

	ZHEJIANG CHANGHONG CAN END MAKING CO.,LTD 浙江昌鸿制盖有限公司	Technical document 技术文件
	SPECIFICATION OF EASY OPEN END 产品规格表	revised on 2017.02.01 修订时间: 2017.02.01

Product parameters of round lid (圆盖系列产品参数)

Spec. 规格		Main dimension and performance 主要尺寸、性能							
Type 盖型	Nominal Dia 公称 直径 (mm)	External diameter 钩边外径 (mm)	Countersink depth 埋头深度 (mm)	Curl height 钩边高度 (mm)	Panel depth 盖面深度 (mm)	Dry compound 干密封胶 (mg)	Buckle test 耐压强度 (kPa)	Pop force 启破力 (N)	Pull force 全开力 (N)
202#	52.3	Φ 61.20±0.10	3.85±0.10	1.85±0.10	3.30±0.10	42±6	≥240	12-26	45-75
209#	62.5	Φ 72.15±0.10	4.75±0.10	1.90±0.10	4.05±0.10	50±7	≥240	12-26	45-75
211#	65.3	Φ 74.75±0.10	4.75±0.10	1.95±0.10	4.05±0.10	54±8	≥240	12-26	45-75
214#	69.9	Φ 79.15±0.10	4.80±0.10	1.95±0.10	3.90±0.10	58±8	≥240	12-26	45-75
300#	72.9	Φ 82.15±0.10	4.80±0.10	1.95±0.10	3.90±0.10	60±8	≥240	12-26	45-75
303#	77.6	Φ 86.70±0.10	4.80±0.10	2.0±0.10	3.90±0.10	65±9	≥200	12-26	45-75
305#	80.3	Φ 90.15±0.10	4.80±0.10	2.05±0.10	3.90±0.10	68±9	≥200	12-26	55-85
307#	83.3	Φ 93.20±0.10	4.63±0.10	2.05±0.10	3.90±0.10	70±10	≥200	12-26	55-85
309#	86.7	Φ 96.45±0.10	4.00±0.10	2.05±0.10	4.00±0.10	78±10	≥180	12-26	85-120
315#	95.5	Φ 105.45±0.10	4.83±0.10	2.05±0.10	3.90±0.10	80±10	≥180	12-26	55-85
401#	98.9	Φ 108.85±0.10	4.83±0.10	2.05±0.10	3.90±0.10	83±10	≥180	12-26	55-85
403#	102.4	Φ 112.15±0.10	3.90±0.10	2.05±0.10	3.90±0.10	92±10	≥120	12-26	85-120

Product parameters of abnormality lid (异形盖系列产品参数)

Spec. 规格		Main dimension and performance 主要尺寸、性能								
Type 盖型	Nominal dimension 公称尺寸 (mm)	External dimension 钩边外径(mm)		Countersink depth 埋头深度 (mm)	Curl height 钩边高度 (mm)	Panel depth 盖面深度 (mm)	Dry compound 干密封胶 (mg)	Buckle test 耐压强度 (kPa)	Pop force 启破力 (N)	Pull force 全开力 (N)
		Long 长边	Short 短边							
501EOE (Ellipse)	145.4×70.8	155.20 ±0.15	80.60 ±0.15	3.08 ±0.15	2.00 ±0.15	4.50 ±0.15	140 ±15	≥150	12-26	75-100
304E EOE (Luncheon meat)	96.8×50.8	106.45 ±0.15	60.50 ±0.15	3.80 ±0.15	1.85 ±0.15	3.80 ±0.15	85 ±10	≥150	12-26	85-110

(工艺) Established by:

(批准) Approved by: